

FORD PICK-UP & VAN

• 460 CUBIC INCH

STANDARD OR POWER STEERING
 WITH OR WITHOUT SMOG PUMP



FM-7003 - PACKING LIST

- FM-7003-1 Compressor mount - 452 Compressor drive belt - FM-7003-2 Compressor mount, rear 7 - 3/8" x 1" NC bolts - 9555300 Crankshaft pulley 4 - 3/8" x 1-1/4" NC bolts - (Std.) Idler pulley $1 - 3/8" \times 1-1/2"$ NC bolt - 1-1/2" Eccentric $1 - 3/8" \times 1-3/4"$ NC bolt - (Std.) Shoulder bolt 1 - 7/16" x 1" NC bolt - 1/16" Idler spacer 1 - 1/2" x 1" NF bolt - 7/16" Mount spacer 1 13 - 3/8" Lockwashers. - 11/16" Mount spacer 1 - 7/16" Lockwasher 3 - 1/4" Mount spacers 4 - 3/8" NC hex nuts

FM-7003 - INSTALLATION INSTRUCTIONS

- 1. Disconnect battery ground cable and remove fan assembly.
- Remove and discard the four original drive pulley bolts. Install the 9555300 crankshaft
 pulley furnished in the kit. Secure with (4) 3/8" x 1" NC bolts with lockwashers.
- 3. Holding mount in approximate position on engine will help identify the proper-bolts to be removed. Remove bolts as indicated on drawing.
- 4. Install the FM-7003-1 front compressor mount to the engine using the proper spacers, bolts and lockwashers as shown in the drawing. Tighten all bolts securely.
- 5. Install the FM-7003-2 rear compressor mount to the engine using (3) 1/4" mount spacers. Use (2) 3/8" x 1" NC bolts with lockwashers in the two inside holes. Use a 7/16" x 1" NC bolt with lockwasher in the outside hole. Tighten all bolts securely.
- 5. Install the compressor to the mount using (4) $3/8^{11} \times 1-1/4^{11}$ NC bolts with lockwashers and nuts.
- 7. Install idler assembly using a 1-1/2" eccentric and a 1/16" idler spacer. Use a 1/2" x 1" NF bolt to fasten the idler assembly to the mount.
- 3. Replace fan assembly. Install belts as shown in the belt wrap diagram. Adjust belts to proper tension and secure.
- . Reconnect battery ground cable.

CAUTION: BEFORE RELEASING VEHICLE TO CUSTOMER-Check all Radiator Hoses, Heater Hoses and Oil Lines to be sure there is proper clearance of Compressor, Compressor Mount and Compressor Clutch.